

1201 Slurry[®]



1201 Slurry[®] is a pre-dispersed, delaminated kaolin produced from a water-fractionated feed with a carefully controlled particle size and platy shape. The plate-like structure provides barrier properties in many applications, such as good enamel holdout, stain resistance, and washability in interior emulsion paint systems. 1201 Slurry is suggested in applications such as:

- Interior Primers and Paints
- Exterior Primers & Paints
- Natural & Synthetic Rubber Goods

TYPICAL PROPERTIES

Source	Sandersville, GA
Whiteness (L Value)*	95
Brightness (G.E. % of MgO)*	89
Particle Size, Median (µm)	0.55
Water (wt. %)	32.5
Hardness (Mohs)	3
Oil Absorption (g/100g%)	45
pH, 20% Solids	7.0
Specific Gravity*	2.58
Refractive Index mean*	1.56
Residue (325 mesh screen) (%)	0.005
Weight per Gallon (lbs)	
Slurry @ 67.5% Solids	14.27
Dry *	21.7

* Results of dried kaolin.

DAT001FGCC
April 2012
©IMERY'S 2012
Sixth Edition
All products are registered
trademarks of IMERY'S

CAS No. 1332-58-7

IMERY'S
100 Mansell Court East
Suite 300
Roswell, GA 30076

General:
Tel: (770) 594.0660
Fax: (770) 645.3384
www.imerys-perfmins.com

Customer Service:
Tel: (888) 277.9636
Fax: (770) 645.3631

IMERY'S is a business name of
IMERY'S Pigments, Inc.,
IMERY'S Kaolin, Inc. and
IMERY'S Marble, Inc.
Registered in the USA.

This information is
believed to be correct.
However, this information
does not constitute any
representation, condition or
warranty, nor do
we guarantee results
to be obtained. All
recommendations and
sales are made on the condition
that we will not be held liable for
any damages resulting from their
use. This provision may
not be changed by any
of our representatives.

