

CP Filler®

CP Filler® is a medium particle size, dry ground marble. It finds applications in abrasives, grouts and putties where whiteness is not critical. CP Filler is found in applications such as:

- Patching Compounds
- Scouring and Scrubbing Compounds
- Industrial Grouts
- Putties
- Mastics

TYPICAL PROPERTIES

Source	Sylacauga, AL	Baltimore, MD
Brightness (Hunter Y)	87	85
CaCO ₃ (%)	94	87
Acid Insolubles (%)	3	5
Moisture (%)	0.15	0.15
Plus 325 Mesh (%)	8	6
Hardness (Mohs)	3	3
Refractive Index, mean	1.6	1.6
Specific Gravity	2.7	2.7
Solid Density (lb/gal)	22.7	22.7
Bulk Density: (lb/ft)		
- Loose	65	65
- Packed	95	95

ISO9001
CERTIFIED



DAT001FGCC
July 2013
©IMERYS 2013
Sixth Edition
All products are registered
trademarks of IMERYS

CAS No. 1317-65-3

IMERYS
100 Mansell Court East
Suite 300
Roswell, GA 30076

General:
Tel: (770) 594.0660
Fax: (770) 645.3384
www.imerys-perfmins.com

Customer Service:
Tel: (888) 277.9636
Fax: (770) 645.3631

IMERYS is a business name of
IMERYS Pigments, Inc.,
IMERYS Kaolin, Inc. and
IMERYS Marble, Inc.
Registered in the USA.

This information is
believed to be correct.
However, this information
does not constitute any
representation, condition or
warranty, nor do
we guarantee results
to be obtained. All
recommendations and
sales are made on the condition
that we will not be held liable for
any damages resulting from their
use. This provision may
not be changed by any
of our representatives.

