

FilmLink® 650

FilmLink® 650 is designed for use in polyolefin blown or cast films. It is an ultrafine calcium carbonate produced from high quality naturally occurring deposits.

The use of a hydrophobic coating coupled with close control of the particle size makes FilmLink 650 an ideal engineered mineral for production of quality films imparting unique end use properties.

PROPERTY	SPECIFICATION	TOLERANCE	UNIT
Mineral Agglomeration Level	0.015	Maximum Value	Mass %
Moisture Absorption Index	0.110	Maximum Value	Mass %
Hard Particle Count*			
- #325 Mesh			

*Properties before surface treatment

ISO9001
CERTIFIED



DAT001FGCC
July 2013
©IMERYS 2013
Seventh Edition
All products are registered
trademarks of IMERYS

CAS No. 1317-65-3

IMERYS
100 Mansell Court East
Suite 300
Roswell, GA 30076

General:
Tel: (770) 594.0660
Fax: (770) 645.3384
www.imerys-perfmins.com

Customer Service:
Tel: (888) 277.9636
Fax: (770) 645.3631

IMERYS is a business name of
IMERYS Pigments, Inc.,
IMERYS Kaolin, Inc. and
IMERYS Marble, Inc.
Registered in the USA.

This information is
believed to be correct.
However, this information
does not constitute any
representation, condition or
warranty, nor do
we guarantee results
to be obtained. All
recommendations and
sales are made on the condition
that we will not be held liable for
any damages resulting from their
use. This provision may
not be changed by any
of our representatives.

