

Gama-Sperse® 255

Gama-Sperse® 255 is a free-flowing, dry ground marble with a controlled intermediate broad particle size distribution and a low 325 mesh residue. Applications include water and solvent-based coatings, powder coatings and polyesters.

- Paints where a flattening agent is required
- Polyester Spray-Ups
- Plastics where a medium to high gloss is needed
- Pultrusion

TYPICAL PROPERTIES

Source	Marble Hill, GA
Brightness (Hunter Y)	92
CaCO ₃ (wt. %)	95
Acid Insolubles (wt. %)	2.0
Moisture (wt.%)	0.12
Plus 325 Mesh (wt. %)	0.03
Mean Particle Size (µm)	11
Hegman	3
Index of refraction	1.6
Specific Gravity	2.7
Solid Density (lb/gal)	22.7
Bulk Density: (lb/ft ³)	
- Loose	55
- Packed	80

ISO9001
CERTIFIED



DAT001FGCC
July 2013
©IMERY'S 2013
Sixth Edition
All products are registered
trademarks of IMERY'S

CAS No. 1317-65-3

IMERY'S
100 Mansell Court East
Suite 300
Roswell, GA 30076

General:
Tel: (770) 594.0660
Fax: (770) 645.3384
www.imerys-perfmins.com

Customer Service:
Tel: (888) 277.9636
Fax: (770) 645.3631

IMERY'S is a business name of
IMERY'S Pigments, Inc.,
IMERY'S Kaolin, Inc. and
IMERY'S Marble, Inc.
Registered in the USA.

This information is
believed to be correct.
However, this information
does not constitute any
representation, condition or
warranty, nor do
we guarantee results
to be obtained. All
recommendations and
sales are made on the condition
that we will not be held liable for
any damages resulting from their
use. This provision may
not be changed by any
of our representatives.