

# Glomax™ JDF



Glomax™ JDF is a fine particle dehydroxylated kaolin with a very closely controlled particle size distribution.

Glomax JDF is designed for oleoresinous and primer paint systems where fast grinding and high hiding are required. Glomax JDF is found in applications such as:

- Oleoresins
- Primer Systems

## TYPICAL PROPERTIES

Source	Sandersville, GA
Whiteness (L Value)	96.5
Brightness (GE % of MgO)	91
Particle Size Distribution (µm)	0.6
Oil Absorption (g/100g)	43
pH, 20% Solids	5.0
Free Moisture (%)	0.5
Surface Area, (B.E.T. Nitrogen m <sup>2</sup> /g)	12.0
Specific Gravity	2.62
Refractive Index	1.62
Weight per Gallon (lbs)	21.91
Residue (325 mesh screen) (%)	0.01

DAT001FGCC  
 June 2012  
 ©IMERY'S 2012  
 Sixth Edition  
 All products are registered  
 trademarks of IMERY'S

CAS No. 92704-41-1

IMERY'S  
 100 Mansell Court East  
 Suite 300  
 Roswell, GA 30076

General:  
 Tel: (770) 594.0660  
 Fax: (770) 645.3384  
[www.imerys-perfmins.com](http://www.imerys-perfmins.com)

Customer Service:  
 Tel: (888) 277.9636  
 Fax: (770) 645.3631

IMERY'S is a business name of  
 IMERY'S Pigments, Inc.,  
 IMERY'S Kaolin, Inc. and  
 IMERY'S Marble, Inc.  
 Registered in the USA.

This information is  
 believed to be correct.  
 However, this information  
 does not constitute any  
 representation, condition or  
 warranty, nor do  
 we guarantee results  
 to be obtained. All  
 recommendations and  
 sales are made on the condition  
 that we will not be held liable for  
 any damages resulting from their  
 use. This provision may  
 not be changed by any  
 of our representatives.

