

XO WHITE™

XO WHITE™ is a dry ground marble with a coarse particle size controlled between 16 and 40 mesh screens. In addition to textured coatings and acid neutralization, XO WHITE is NSF registered for use in water filtration systems. XO WHITE is suited for use in the following applications:

- Textured Coatings & Stuccos for Interior & Exterior Use
- Acid Neutralization
- Water Filtration System (NSF listed) *

TYPICAL PROPERTIES

Source	Marble Hill, GA
CaCO ₃ (wt. %)	94
Acid Insolubles (wt. %)	2
Moisture (wt. %)	0.15
Plus 16 Mesh (wt. %)	1
Minus 40 Mesh (wt. %)	10
Hardness (µm)	3
Refractive Index, mean	1.6
Specific Gravity	2.7
Solid Density (lb/gal)	22.7
Bulk Density: (lb/ft)	
- Loose	90
- Packed	105

ISO9001
CERTIFIED



DAT001FGCC
August 2013
©IMERY'S 2013
Seventh Edition
All products are registered
trademarks of IMERY'S

CAS No. 1317-65-3

IMERY'S
100 Mansell Court East
Suite 300
Roswell, GA 30076

General:
Tel: (770) 594.0660
Fax: (770) 645.3384
www.imerys-perfmins.com

Customer Service:
Tel: (888) 277.9636
Fax: (770) 645.3631

IMERY'S is a business name of
IMERY'S Pigments, Inc.,
IMERY'S Kaolin, Inc. and
IMERY'S Marble, Inc.
Registered in the USA.

This information is
believed to be correct.
However, this information
does not constitute any
representation, condition or
warranty, nor do
we guarantee results
to be obtained. All
recommendations and
sales are made on the condition
that we will not be held liable for
any damages resulting from their
use. This provision may
not be changed by any
of our representatives.