

# Z White™

Z White™ is a dry ground marble with a coarse particle size that is controlled between 10 and 20 mesh screens. Textured coatings and water treatment are the main applications. Z White is found in applications such as:

- Textured Coatings & Stuccos based on Cement or Acrylics
- Acid Neutralization
- Water Filtration System (NSF Listed)

## TYPICAL PROPERTIES

Source	Marble Hill, GA
CaCO <sub>3</sub> (wt. %)	95
Acid Insolubles (wt. %)	2
Moisture (wt. %)	0.15
Plus 10 Mesh (%)	1
Minus 20 Mesh (%)	7
Hardness (µm)	3
Refractive Index, mean	1.6
Specific Gravity	2.7
Solid Density (lb/gal)	22.7
Bulk Density: (lb/ft)	
- Loose	90
- Packed	105

**ISO9001**  
CERTIFIED



DAT001FGCC1  
August 2013  
©IMERY'S 2013  
Seventh Edition  
All products are registered  
trademarks of IMERY'S

CAS No. 1317-65-3

IMERY'S  
100 Mansell Court East  
Suite 300  
Roswell, GA 30076

General:  
Tel: (770) 594.0660  
Fax: (770) 645.3384  
[www.imerys-perfmins.com](http://www.imerys-perfmins.com)

Customer Service:  
Tel: (888) 277.9636  
Fax: (770) 645.3631

IMERY'S is a business name of  
IMERY'S Pigments, Inc.,  
IMERY'S Kaolin, Inc. and  
IMERY'S Marble, Inc.  
Registered in the USA.

This information is  
believed to be correct.  
However, this information  
does not constitute any  
representation, condition or  
warranty, nor do  
we guarantee results  
to be obtained. All  
recommendations and  
sales are made on the condition  
that we will not be held liable for  
any damages resulting from their  
use. This provision may  
not be changed by any  
of our representatives.

